

**Steel jamb backfilling requirements**

Notes: **Type 7 Split jambs do not need to be backfilled.**

**Type 5 and 6 jambs for Masonry OR GIB walls**

	-/30/-	-/30/30	-/60/-	-/60/30	-/60/60 triboard only	-/90/-	-/90/30	-/120/-	-/120/30	-/240/-	-/240/30
upto 2400 x 1200	NO	YES	NO	YES	YES	NO	YES	NO	YES	NO	YES
over 2400	NO	YES	NO	YES	YES	NO	YES	NO	YES	NO	YES
upto 2400 x 1200/1200 PAIR	NO	YES	NO	YES	YES	NO	YES	NO	YES	NO	YES
over 2400 x 1200/1200 PAIR	NO	YES	NO	YES	YES	NO	YES	NO	YES	NO	YES

**Speedwall jambs**

	-/30/-	-/30/30	-/60/-	-/60/30	-/60/60 triboard only	-/90/-	-/90/30	-/120/-	-/120/30	-/240/-	-/240/30
upto 2400 x 1200	NO	YES	NO	YES	YES	NO	YES	NO	YES	cant make in speedwall	cant make in speedwall
upto 2400 x 1200/1200 PAIR	NO	YES	NO	YES	YES	NO	YES	NO	YES	cant make in speedwall	cant make in speedwall